

Detailed Specifications



CopyCentre 265 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Offset Catch Tray



WorkCentre 265 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Office Finisher



WorkCentre 275 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Advanced Office Finisher



WorkCentre Pro 275 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Professional Finisher

CopyCentre/WorkCentre/WorkCentre Pro 265

CopyCentre/WorkCentre/WorkCentre Pro 275

OUTPUT SPEED – printing and copying

Up to 65 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm)	Up to 75 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm)
Up to 49 ipm 8.5 x 14 in. (216 x 356 mm)	Up to 49 ipm 8.5 x 14 in. (216 x 356 mm)
Up to 42 ipm 11 x 17 in. (A3/297 x 420 mm)	Up to 42 ipm 11 x 17 in. (A3/297 x 420 mm)

FIRST-IMAGE-OUT TIME (FCOT) – letter size, from platen to offset catch tray

As fast as 2.7 seconds

As fast as 2.7 seconds

Copy Specifications

COPYING

Document Scanner	Duplex Automatic Document Handler (DADH) 75-sheet capacity. Scans sizes up to 11 x 17 in. (A3/297 x 420 mm) SEF
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 9,999
Resolution	600 x 600 x 8 bit dpi input / 4800 x 1200 dpi interpolated output
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)
Copy Pre-Collation Memory (EPC)	256 MB — CopyCentre (expandable to 512 MB) 256 MB — WorkCentre (expandable to 512 MB) 512 MB — WorkCentre Pro

Continued

Copy Specifications

COPYING (Continued)	Features	Options
Basic Copy Features/Options	Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Hole Punching Stapling Booklet Creation
Imaging Copy Features	Image Quality <ul style="list-style-type: none"> • Original Type Selections: Normal, Text, Halftone, Photo • Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening Book Copying/Bound Copying Edge Erase (with Print to Edge option) Mixed Size Original Image Shift (with Auto Center option)	
Output Copy Features	Transparencies (including dividers – blank or printed) Booklet Creation Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Covers (Front only, Front and Back, Back only: Blank or Printed) Annotation and Bates Stamping Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and Recall job programming) Heavy weight paper (not rough stock)	
Other Copy/Device Features	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Internal Auditron (Copy) Languages (Select up to 20 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)	
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)	
Foreign Device Interface (FDI) (Optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service	
USB Port	PC interface for upload/download of internal auditron data and Xerox Copier Assistant Customer device administration/software upgrade	

Continued

Copy Specifications

COPYING (Continued)

Accessibility Option Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.

PAPER HANDLING – Duplex Automatic Document Feeder (DADF)

Capacity*	75 sheets
Speed	265/275: Up to 75 ipm (images per minute), 8.5 x 11 in. (A4/210 x 297 mm) long edge feed (LEF)
Paper Sizes Sensed	Statement – 5.5 x 8.5 in. (A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF
Weights	13 lb to 32 lb bond (50 to 120 gsm)

PAPER HANDLING – Two Front Loading Paper Trays

Capacity*	550 sheets each
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Custom Settings (up to 7)

PAPER HANDLING – Bypass Tray

Capacity*	100 sheets
Sizes	User Adjustable from 4.13 x 5.83 in. (105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

Continued

*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

Copy Specifications

PAPER HANDLING – Bypass Tray (Continued)

Types	Letterhead	Label Stock
	Preprinted forms	Transparencies
	Plain Paper	Tab Stock
	Drilled/Hole-punched	Bond
	Heavyweight	Custom Settings (up to 7)
	Recycled	

PAPER HANDLING – High Capacity Feeder (HCF)

Capacity*	Two trays: 1,600 and 2,000 sheets each
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)

PAPER HANDLING – Total Capacity

Device Total Capacity*	4,800 sheets (with Bypass tray, front loading paper trays and High Capacity Feeder)
-------------------------------	---

OUTPUT OPTION – Offset Catch Tray (OCT) option (265 only)

Capacity*	300 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

OUTPUT OPTION – Office Finisher option

Capacity*	Top Tray — 250 sheets
	Stacking Tray — 2,000 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling*	50 sheets Single (any corner) and dual

Hole Punch (Optional)	North America
	3-hole punch
	2-hole Legal punch

Europe
2-hole punch
4-hole punch
4-hole “Swedish” punch

OUTPUT OPTION – Advanced Finisher option

Capacity*	Top Tray — 250 sheets
	Stacking Tray — 3,000 sheets (2 x 1,500)

Continued

*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

Copy Specifications

OUTPUT OPTION – Advanced Finisher option (Continued)

Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
Stapling*	50 sheets Single (any corner) and dual	
Hole Punch (Standard)	North America 3-hole punch - Standard	Europe 2-hole punch - Standard
Hole Punch (Optional)	2-hole Legal punch	4-hole punch 4-hole “Swedish” punch

OUTPUT OPTION – Professional Finisher option

Capacity*	Top Tray — 250 sheets Stacking Tray — 1,500 sheets	
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
Stapling*	50 sheets Single (any corner), dual, front, rear, SEF and 4-stitch	
Hole Punch (standard)	North America 3-hole punch	Europe 2-hole punch
Hole Punch (optional)	2-hole Legal punch	4-hole punch 4-hole “Swedish” punch

Booklet Maker	Capacity* <ul style="list-style-type: none"> • Tray stop up: 30 booklets (1-15 sheets per booklet) • Tray stop down: Unlimited
	Sizes <ul style="list-style-type: none"> • Letter — 8.5 x 11 in. (A4/210 x 297 mm) • Legal — 8.5 x 14 in. (216 x 356 mm) • Ledger — 11 x 17 in. (A3/297 x 420 mm)
	Weights <ul style="list-style-type: none"> • 16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
	Stapling* <ul style="list-style-type: none"> • Saddle-stitch (2-15 sheets / 8-60 page booklet)
	Folding <ul style="list-style-type: none"> • V-folding (1-15 sheets / unstapled)

Continued

*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.

Copy Specifications

OUTPUT OPTION – Convenience Stapler option

Capacity* 50 sheets

Print Specifications

NETWORK PRINTING – Smart Controller (*Simultaneous rip, receive, program ahead, queue processing, and transmit*)

Processor 1.4 GHz AMD Athlon dedicated

Memory (ESS) WorkCentre 128 MB (expandable to 256MB),
WorkCentre Pro 256 MB

System Disk 80 GB Hard Drive shared

**Printer Language (PDL)
auto switching****WorkCentre**

- PCL 6/PCL 5e
Standard in North America only:
- PostScript 3 emulation
- TIFF (6.0 Old JPEG and New JPEG)
- TIFF Fax Extended (TIFF - FX)
- PDF
- LCDS, SCS, XES and IPDS
through third party transforms

WorkCentre Pro

- PCL 6/PCL 5e
- PostScript 3 emulation
- TIFF (6.0 Old JPEG and New JPEG)
- TIFF Fax Extended (TIFF - FX)
- PDF
- LCDS, SCS, XES and IPDS
through third party transforms

NETWORK PRINTING – Resolution (*printing via CentreWare Software*)

PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey)
PCL: 600 x 600 dpi
Supports PCL and PS switching within job

NETWORK PRINTING – Printing Features

Bi-directional Print Drivers
Embedded web server for remote control/monitor/setup
Job monitoring at the device and at desktop

Advanced Features Include: Special font
Banner Sheet
Rotate Image
Offset

Continued

*Paper capacities are based on 20 lb bond stock; capacities will vary with different weight stocks.
**Features, configurations and options may vary by location.

Print Specifications

NETWORK PRINTING – Print Driver Options

Paper Output

Job Type

- Secure, Sample, Delay
- LAN Fax-with fax option
- Save and Save & Print – WorkCentre Pro*

Paper Selection by attribute (including transparency separators)

Duplex (2-sided)

Finishing

- Multiple stapling positions
- Hole punch (if configured)
- Booklet creation
- Fit to new paper size
- Saddle stitch with Professional finisher

Output tray selections

Store and recall driver setting

Special Pages

Exception page programming (covers, inserts/tabs, exception pages)

Image Options

Light/Dark

Toner saver

Resolution options (600 x 600 and 1200 x 1200 dpi)

Reduction/Enlargement

Margins (edge to edge printing)

Invert Image (negative/mirror)

Layout/Watermark

N-up (16)/Multi-up

Booklet Layout/Finishing

Fit to new paper size

Image orientation

Watermark options

PRINT PROTOCOLS AND NETWORKS

Physical

Ethernet 10/100BaseT, 10BaseT, 10Base2 (IEEE802.5) (Token ring) –via adapter, wireless Ethernet (IEEE802.11a/b/g)
-via third party adapter

USB 2.0 / (IEEE1284) Parallel Port Kit (WorkCentre Pro option)

Operating Systems

WorkCentre

- Microsoft Windows 98, Me, NT 4.0, 2000, XP, Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6
- Standard in North America :
- Mac OS 8.x, 9.x, OS X, 10.3 and higher
- Solaris 2.8, 2.9, 2.10
- HPUX 11.0
- IBM AIX 4.3.3
- Linux Fedora Core 1 (Intel)
- Linux Yellowdog 3.0

WorkCentre Pro

- Microsoft Windows 98, Me, NT 4.0, 2000, XP, Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6
- Mac OS 8.x, 9.x, OS X
- Solaris 2.8, 2.9, 2.10
- HPUX 11.0
- IBM AIX 4.3.3
- Linux Fedora Core 1 (Intel)
- Linux Yellowdog 3.0

Continued

*Feature is not included with the Common Criteria Security Option.

Print Specifications

PRINT PROTOCOLS AND NETWORKS (Continued)

Network Protocols

WorkCentre

- TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS®/NEPS
- AppleTalk / EtherTalk, Bonjour enabled via PostScript- (standard in North America)

WorkCentre Pro

- TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS®/NEPS
- AppleTalk/EtherTalk, Bonjour

Administration Protocols

DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP, DHCP Autonet

Security Protocols/Features

Protocols

- HTTPS
- IPsec
- 802.1x

Features

- IP filtering
- Unlimited Secure Print
- Audit log
- Image Overwrite
- LDAP Secure Authentication / Secure LDAP
- Data Encryption

Fonts

PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts)

PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table)

Font Management Utility for downloading additional fonts (available for Windows and Mac)

Print Drivers

Environment

PCL6/5e

PostScript 3

Windows 98/Me, NT 4.0, 2000/XP,
Windows Server 2003, Windows
Walk-up (PS), Microsoft Certified

Xerox custom graphical user interface
Bi-directional features

- Job, Paper and Toner status
- Job status notification
- Just in time Bi-Di
- Auto population of IP address
- Delete jobs

Xerox custom graphical user interface
Bi-directional features

- Job, Paper and Toner status
- Job status notification
- Just in time Bi-Di
- Auto population of IP address
- Delete jobs

Macintosh System 8.x – 10.2

N/A

Generic PPD

Macintosh System 10.3 and higher

N/A

Xerox custom graphical user interface
Bi-directional features

- Toner, Fuser and Xerographic module status

Continued

Print Specifications

PRINT PROTOCOLS AND NETWORKS (Continued)

<i>Print Submission Tools</i>	<i>Environment</i>	<i>PCL</i>	<i>PostScript 3</i>
	Solaris 2.8, 2.9, 2.10; HPUX 11.0, IBM AIX 4.3.3; Linux Fedora Core 1 (Intel); Linux YellowDog 3.0	Submission Tool only	Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 98/Me/NT 4.0/2000/XP, Windows Server 2003	Submission Tool for any TIFF or PDF file	N/A
DEVICE MANAGEMENT			
<i>Management Support</i>	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2		
<i>Xerox CentreWare Internet Services</i>	Allows simple remote installation setting of configuration options and management of the device		
<i>Xerox CentreWare Web</i>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher		
<i>Novell NDPS/NEPS (gateway for WorkCentre Pro)</i>	Server gateway application: centralized management tool		
<i>Xerox CentreWare for Unicenter TNG</i>	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View		
<i>Xerox CentreWare for Tivoli NetView</i>	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by Tivoli NetView		
<i>Xerox CentreWare for HP OpenView</i>	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView		
<i>Xerox Barcode Pro PS (optional)</i> Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.		

Continued

Print Specifications

DEVICE MANAGEMENT (Continued)

<p>Xerox Device Types for SAP R/3 Environment are available at www.xeroxofficesapsolutions.com</p>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre Pro • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
<p>Xerox SAP R/3 Intelligent Barcode Utility (optional) Purchase via www.font.net</p>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.</p>

CENTREWARE INTERNET SERVICES – Integrated device Web page

<p>Device Status</p>	<p>Web server embedded on SMart Controller</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
<p>Job-Print Queue Viewing</p>	<p>Complete job print queue management –delete</p>
<p>Job Submission</p>	<p>Print ready files PS, PCL (TIFF, PDF with WorkCentre Pro only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)</p>
<p>Device Administration</p>	<p>Allows simple, remote installation setting of configuration options and management of the device</p>
<p>Scan Template Management</p>	<p>250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning</p>
<p>Browsers</p>	<p>Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x Safari 1.x Mozilla Firefox 1.x</p>
<p>Support</p>	<p>Online support available via web page</p>

Continued

Scan Specifications

SCANNING

Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Input Speed	Scan at 75 ipm 265/275 - 8.5 x 11 in. (A4/210 x 297 mm) LEF at all resolutions
Resolutions <i>DPI Options</i>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
Scan Presets	<ul style="list-style-type: none"> • Archival Record (Normal Quality - Smallest file size) – 100 x 100 • For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 • For High Quality Printing (High Quality - Large file size) – 300 x 300 • For OCR (High Quality - Large file size) – 300 x 300 • Simple Scan (Normal Quality - Small file size) – 200 x 200
Quality/File Size	<ul style="list-style-type: none"> • Normal Quality (Small file size) • Higher Quality (Large file size) • Maximum Quality (Largest file size)
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
File Formats	TIFF 6.0 with G3 MH, G4 MMR, MRC or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, JPEG or JBIG2 compression) Linearized PDF*
SCAN TO EMAIL (Optional with WorkCentre / Standard with WorkCentre Pro)	
Capability	Scan to email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options

Continued

*Feature is not included with the Common Criteria Security Option.

Scan Specifications

NETWORK SCANNING (Standard with WorkCentre Pro)

Capability	<ul style="list-style-type: none"> Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services Scan to Home displays one template and populates with the user's directory path after authentication* Scan to file Scan to network server / directory Scan to Mailbox* Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com
Network Protocol	<p>Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS</p>
Document Management Fields (Metadata)	<p>Features only available in Network Scan to File Templates: 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template - Metadata Fields consists of field name, display at the LUI or not, default value and other configurations Customized fields viewed on user interface Variable data entered using virtual keyboard at device</p>
Scan Template Management	<p>Share scan templates among WorkCentre Pro via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option</p>
Scan Features	<p>Build job (for scan to file only)(enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge.</p>

NETWORK SCANNING SOFTWARE SOLUTIONS with WorkCentre Pro

FreeFlow Scan to PC Desktop Workgroup Edition SE V 8.0 (optional)	<p>A desktop offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort SE 10 – image viewing and file management software ScanSoft OmniPage SE 4.0– offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre Pro to individual desktops</p>
FreeFlow Scan to PC Desktop Workgroup Edition Professional V 8.0 (optional)	<p>A desktop offering that provides advanced document imaging, archiving, editing and organization tools. ScanSoft PaperPort Professional 10 image viewing and file management software</p> <ul style="list-style-type: none"> Complete PDF functionality Secure PDF workflow of all scanning applications <p>ScanSoft OmniPage Pro 15 Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops. Also includes an email inbox polling capability</p>

Continued

*Feature is not included with the Common Criteria Security Option.

Scan Specifications

NETWORK SCANNING SOFTWARE OPTIONS with WorkCentre Pro (Continued)

FreeFlow SMARTsend (optional)	<p>Server base document routing software that supports multiple scan-enabled multifunctional systems Enables transformation, distribution and routing of scanned documents Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including PDF, workflow settings, workflow summary)</p> <ul style="list-style-type: none"> • Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site <p>Workflow initiation via device scanning user interface (template selection at device UI) Adding of Metadata information</p>
FreeFlow SMARTsend Professional (optional)	<p>Everything in Free Flow SMARTsend, plus:</p> <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Searchable PDF • Scan to Internet fax file destination • TrueMatch patented search technology

Fax Specifications

FAX OPTIONS –Walk-up option (One or Two Lines options)

Compatibility	ITU (CCITT) Group 3
Memory	32MB (One Line) 256MB (Two Line)
Speed/Modem(s)	1 or 2 V.34 modems: 33,600bps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/G3/Super G3
Fax Send Features	<p>Quality/Resolution</p> <ul style="list-style-type: none"> • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax - off Platen, mixed sizes or Bound/Book <p>Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce/Split large documents Cover letter Delayed send Build Job (up to 1000 images) Polling</p>
Fax Receive Features	<p>One or two-sided printing Stapled or unstapled, hole punch Receive print mode --Manual (size, margin, stock, header)/Auto Auto answer delay Secure receive Junk fax prevention</p>

Continued

Fax Specifications

FAX OPTIONS –Walk-up option (One or Two Lines options) (Continued)

Fax Reports	Activity Dial directory Group directory Options Pending Jobs
Fax Mailboxes	Up to 100 password-protected Poll Remote mailboxes (up to 255) password-protected
Auto Dialing Features	Speed Dials <ul style="list-style-type: none"> • 200 (One-line option) • 1,000 (Two-line option) Group Dials <ul style="list-style-type: none"> • Up to 100 groups with up to 200 recipients per group (One-line option) • Up to 200 groups with up to 400 recipients per group (Two-line option) Auto redial <ul style="list-style-type: none"> • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
Resolutions	200 x 100 dpi (Standard) 400 x 400 dpi 200 x 200 dpi (Fine) 400 x 600 dpi 300 x 300 dpi 600 x 600 dpi (Super fine) 200 x 400 dpi

FAX OPTIONS - LAN Fax with Walkup Fax (Optional with WorkCentre and WorkCentre Pro)

Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers)
Recipient options (add recipient or add from phone book)
User personal phone book – up to 1,000 entries
Confirmation sheet
Send speed (14.4/33.6kbps or 4800bps)
Send time
Dialing options (prefix or credit card)
Cover sheet (add notes)
Preferences – Phonebook (personal or shared LDAP)

FAX OPTIONS – Internet Fax (Optional with WorkCentre Pro)

Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF

Continued

Fax Specifications

FAX OPTIONS – Internet Fax (*Optional with WorkCentre Pro*) (Continued)

Resolutions	600 x 600 dpi	200 x 100 dpi
	400 x 400 dpi	100 x 100 dpi
	300 x 300 dpi	72 x 72 dpi
	200 x 200 dpi	
Network Protocols	SMTP POP3 (RFC 1939)	
Compliance	ITU-T T.37 complaint	
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body 	

FAX OPTIONS – Network Fax Server Enablement (*Optional with WorkCentre Pro*)

Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).	
Maximum Scan Size	11 x 17 in. (A3/297 x 420mm)	
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP	
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm)) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)	
Fax Print Features	One – or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)	
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Business Alliance Partner Program. For details visit www.xerox.com	

Continued

Device Management Specifications

ACCOUNTING FEATURES – Internal Auditor

Tracking	Copy usage
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts
Features	Auditron report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software

ACCOUNTING FEATURES – Xerox Standard Accounting (*Standard with WorkCentre and WorkCentre Pro*)

Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.

ACCOUNTING OPTIONS – Network Accounting (*Optional on WorkCentre Pro*)

Enhanced network accounting with up to the minute data on how the WorkCentre Pro system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Business Alliance Partner solutions. For details visit www.xerox.com
Security enhancements with the addition of HTTPS protocol support
WorkCentre Pro requests account authentication from 3rd party server enabling larger databases of users and accounts

SECURITY – review the supplemental Security brochure for details

Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) PIN-based guest login
Features	802.1x* HTTPS (SSL) SNMP V3 IPSec Network Authentication Device Access Password Protection IP Filtering Audit Log Disk Encryption – for Store Print and Scan to Mailbox features on WorkCentre Pro* Secure Print Fax Security

Continued

*Feature is not included with the Common Criteria Security Option.

Device Management Specifications

SECURITY – review the supplemental Security brochure for details *(Continued)*

Options

Disk Image Overwrite

-Immediate, On Demand, and Scheduled

Common Criteria Certified Software Level

-Provides the exact certified software level that was certified by the National Information Assurance Partnership. This software level does not include the items noted in this document with an “**”.

XEROX EXTENSIBLE INTERFACE PLATFORM™ (EIP)

Xerox EIP is a development platform that allows customers, Xerox Business Partners and System Integrators to build unique applications that are presented at the WCP 200 series user interface. Xerox EIP is an open standard platform that utilizes industry standard development tools enabling applications that are easily developed and customized to meet the needs of any business environment or personalized for each user. These applications will yield simpler user interactions and result in less time interacting with the MFP which drives increased worker productivity and systems that easily adapt to your business processes.

Machine Specifications

MONTHLY DUTY CYCLE

265 – up to 250,000 pages

275 – up to 300,000 pages

BASIC CONFIGURATIONS**

CopyCentre, WorkCentre and WorkCentre Pro with DADF and HCF

Continued

*Feature is not included with the Common Criteria Security Option.

**Features, configurations and options may vary by location.

Machine Specifications

ACCESSORY OPTIONS**

CopyCentre

Walkup Fax • One line
 • Two lines

Offset Catch Tray (OCT) (265 only)

Office Finisher

Advanced Office Finisher

Professional Finisher

Convenience Stapler

Hole Punch (with Office Finisher — see Output Options for details)

256 MB Pre Collation Memory (EPC) (CC/WC only)

Foreign Interface Device (FDI)

Xerox Copier Assistant (XCA)

Upgrade Kits to WorkCentre or WorkCentre Pro

WorkCentre — same as
CopyCentre, plus:

Walkup Fax with LAN Fax • One line
 • Two lines

PostScript 3 emulation/MAC Ethertalk (standard in North America)

Image Overwrite Security (standard feature in North America)

Email with LDAP/Authentication and additional memory

Common Criteria Certified Software Level

Common Criteria Kit (US only)

WorkCentre Pro — same
as CopyCentre plus:

Walkup Fax with LAN Fax • One line
 • Two lines

Image Overwrite Security (standard feature in North America)

USB 2.0 / (IEEE1284) Parallel Port Kit

FreeFlow Scan to PC Desktop SE and Professional

Internet Fax

Enablement for Fax/Scan/Accounting Xerox Business Alliance Partner solutions

Common Criteria Certified Software Level

Common Criteria Kit (US only)

ELECTRICAL REQUIREMENTS

110-140 Volt Nominal, 60 Hz, 20A (North America)

220-240 Volt Nominal, 50 Hz, 10A (Europe)

Note: Convenience Stapler requires separate 110V 15A circuit

Continued
 **Features, configurations and options may vary by location.

Machine Specifications

POWER CONSUMPTION ¹	CopyCentre	WorkCentre / WorkCentre Pro
<i>Running</i>	≤ 1690 ¹ watts	≤ 1740 ¹ watts
<i>Standby</i>	≤ 280 watts	≤ 310 watts
<i>Low Power Mode</i>	≤ 130 watts	≤ 160 watt
<i>Auto Off / Sleep mode</i>	≤ 5 watts	≤ 9 watts
<i>Warm-up Ready to Copy</i>	≤ 28 seconds	≤ 28 seconds
<i>Warm-up Ready to Print</i>	NA	≤ 130 seconds
<i>Low Power Recovery</i>	≤ 20 seconds	≤ 20 seconds

ENVIRONMENTAL CONSIDERATIONS

Required Temperature Range 10° to 32° C

Required Relative Humidity 10% to 85%

DIMENSIONS AND WEIGHTS (CopyCentre)	Width	Depth	Height ³	Weight ²
<i>Configuration With OCT (265 only)</i>	40 in. / 1,012 mm	28 in. / 710 mm	57 in. / 1,460 mm	275 lbs / 125 kg
<i>With Office Finisher</i>	50 in. / 1,271 mm	28 in. / 710 mm	57 in. / 1,460 mm	337 lbs / 153 kg
<i>With Advanced Office Finisher</i>	56 in. / 1,412 mm	28 in. / 710 mm	57 in. / 1,460 mm	443 lbs / 201 kg
<i>With Professional Finisher</i>	58 in. / 1,477 mm	28 in. / 710 mm	57 in. / 1,460 mm	443 lbs / 201 kg

DIMENSIONS AND WEIGHTS (WorkCentre / WorkCentre Pro)	Width	Depth	Height ³	Weight ²
<i>Configuration With OCT (265 only)</i>	51 in. / 1,297 mm	34 in. / 875 mm	57 in. / 1,460 mm	295 lbs / 134 kg
<i>With Office Finisher</i>	61 in. / 1,556 mm	34 in. / 875 mm	57 in. / 1,460 mm	358 lbs / 162 kg
<i>With Advanced Office Finisher</i>	67 in. / 1,697 mm	34 in. / 875 mm	57 in. / 1,460 mm	463 lbs / 210 kg
<i>With Professional Finisher</i>	69 in. / 1,762 mm	34 in. / 875 mm	57 in. / 1,460 mm	463 lbs / 210 kg

SPACE REQUIREMENTS (Fixed)	Width	Depth	Height
<i>Configuration With OCT (265 only)</i>	119 in. / 3,023 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. / 2,718 mm 108 in. / 2,743 mm
<i>With Office Finisher</i>	129 in. / 3,276 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. / 2,718 mm 108 in. / 2,743 mm
<i>With Advanced Office Finisher</i>	134 in. / 3,403 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. / 2,718 mm 108 in. / 2,743 mm
<i>With Professional Finisher</i>	137 in. / 3,480 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. / 2,718 mm 108 in. / 2,743 mm

Continued

¹ With Office Finisher. ² Weights do not include Rear Wall (3.78 lbs. / 1.72 kg) or Shelf (2.99 lbs. / 1.36 kg). ³ Height with DADH raised.

Machine Specifications

SPACE REQUIREMENTS (Moveable)	Width	Depth	Height
<i>Configuration With OCT (265 only)</i>	79 in. / 2,012 mm	CopyCentre WorkCentre/ WorkCentre Pro 67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm
<i>With Office Finisher</i>	89 in. / 2,271 mm	CopyCentre WorkCentre/ WorkCentre Pro 67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm
<i>With Advanced Office Finisher</i>	95 in. / 2,412 mm	CopyCentre WorkCentre/ WorkCentre Pro 67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm
<i>With Professional Finisher</i>	98 in. / 2,477 mm	CopyCentre WorkCentre/ WorkCentre Pro 67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm

CERTIFICATIONS

FCC Class A Compliant (US), DOC Class A Compliant (Canada)
89/336/EEC (Europe)
UL Listed (UL 1950, Third Edition)
CB Certified (IEC 60950/EN 60950)
73/23/EEC (Europe)
95/5/EEC (Europe)
Energy Star

SUPPLIES

Description	Order Number	No. per Box	Expected Yield
Toner Cartridge	6R01146	2	45,000 at 6% area coverage
Waste Toner Bottle (supplied with each toner cartridge box)		1	100,000
Staple Cartridge (for Office Finisher/Advanced Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
Staple Cartridge (for Booklet maker saddle-stitch stapling)	8R12897	8 (4 x 2)	2,000 per cartridge (16,000 staples)
Staple Cartridge (for Convenience Stapler)			
• Complete Cartridge	8R12964	1	5,000 per cartridge
• Refill Cartridge	8R12941	3	5,000 per cartridge (15,000 staples)

SMART KITS

Fuser Module (includes ozone filter)			
North America	109R00723	1	400,000
Europe	109R00724	1	400,000
Xerographic Module - Metered	113R00672	1	400,000
Xerographic Module - Sold	113R00674	1	400,000
Document Handler Feeder Rolls	113R00686	1	150,000 feeds

