

# SF-560R

# SF-565PR

## Business Class Laser MFPs

- Fast Super G3 33.6 Kbps fax modem
- 3 sec./page transmission speed (approx.)
- Fax battery backup up to 96 hours (4 days)
- 2 MB fax memory (approx. 160 pages)
- Speeds up to 17 cpm, 17 ppm
- 250-sheet cassette, 30-sheet ADF
- USB 2.0 connectivity (SF-565PR)
- Windows and Linux compatible (SF-565PR via USB)

Imagine getting all your work done in eight hours. The Samsung SF-560R and SF-565PR laser MFPs can help. Powerful G3 33.6 Kbps modems send your faxes out at a rate of just 3 seconds per page. Integrated digital copiers copy at speeds up to 17 cpm. The SF-565PR adds 17 ppm laser printing for crisp, professional documents. And both offer scanning capability, so you can digitize and quickly print or fax, all from a single compact machine. They're machines that get the work done. With the Samsung SF-560R and SF-565PR laser fax machines, it's not hard to imagine.



# SF-560R SF-565PR



## SF-560R Fax/Copy/Scan SF-565PR Fax/Copy/Scan/Print

### Features

#### Fast Faxing

Powerful Super G3 33.6 Kbps modem for fast 3-second transmission speed.

#### More Fax Options

Fax to several locations. Forward incoming faxes to your hotel. Set a password to receive incoming faxes. And more.

#### TollSave™

The SF-565PR lets you schedule large faxes to be sent during off-hours, when toll charges are less.

#### Dependable Battery Backup

Even if the power goes down, you can still receive and store fax data for up to 96 hours.

#### Fast Copying

Copy at 300 dpi at speeds up to 17 ppm. You can also resize documents from 50% – 200% of your original.

#### Scanning and Printing

The SF-565PR increases your versatility by adding the ability to digitize documents, then fax or print them.

#### TonerSave™

With the touch of a button, Samsung TonerSave™ extends cartridge life by up to 40%.

#### Dimensions SF-565PR



### Specifications

#### SF-560R

#### SF-565PR

Specifications	SF-560R	SF-565PR
<b>Laser Fax</b>		
Modem Speed	Super G3 33.6 Kbps	Super G3 33.6 Kbps
Transmission Speed	Approximately 3 Seconds Per Page	Approximately 3 Seconds Per Page
Scan Speed	Approximately 6 Seconds Per Page	Approximately 6 Seconds Per Page
Compression Code	MH/MR/MMR (ECM Mode)	MH/MR/MMR (ECM Mode)
Fax Memory	2 MB (Approx. 160 pages)	2 MB (Approx. 160 Pages)
Fax Compatibility	ITU-T Group 3, ECM	ITU-T Group 3, ECM
Resolution (Up To)	203 x 392 dpi	203 x 392 dpi
Battery Backup	4 Days (Up To 96 Hours)	4 Days (Up To 96 Hours)
Speed Dial	Up To 80 Locations	Up To 80 Locations
One-Touch Dial	Up To 20 Locations	Up To 20 Locations
Other Features	Rx Polling, Security (Incoming Fax)	TollSave, Rx Polling, Security (Incoming Fax)
<b>Laser Printer</b>		
Technology		Laser
Print Speed (Up To)		17 ppm
Print Resolution		600 x 600 dpi
Printer Memory		8 MB
Print Language		SPL (GDI Equivalent)
Connectivity		USB 2.0
Supported OS		Windows 2000, XP, Vista and Various Linux Systems (Via USB Only)
<b>Digital Copier</b>		
Copy Speed (Up To)	17 cpm	17 cpm
Resolution	300 x 300 dpi	300 x 300 dpi
Reduction/Enlargement	50 – 200%	50 – 200%
Multiple Copy	1 – 99 Copies	1 – 99 Copies
<b>Scanner</b>		
Type	Sheet-Fed	Sheet-Fed
Method	CIS, Mono	CIS, Mono
Resolution (Optical, Enhanced)	200 x 200 dpi (300 x 300 dpi)	200 x 200 dpi (300 x 300 dpi)
Scan Size	15.7" x 8.2"	15.7" x 8.2"
Grayscale	256 Levels	256 Levels
<b>Paper Handling</b>		
Standard Cassette	250 Sheets	250 Sheets
Multipurpose Tray	1 Sheet	1 Sheet
Output Tray	150 Sheets	150 Sheets
Automatic Document Feeder	30 Sheets	30 Sheets
Media Types	Plain Paper	Plain Paper
Media Size (Up To)	Letter and Legal	Letter and Legal
Paper Weight	Cassette: 16 – 28 Lbs., Bypass: 16 – 43 Lbs.	Cassette: 16 – 28 Lbs., Bypass: 16 – 43 Lbs.
<b>Consumables</b>		
Toner Type	1 Piece Toner Cartridge (SF-D560RA)	1 Piece Toner Cartridge (SF-D560RA)
Toner Yield At 5% Coverage	3,000 Letter-Size Pages (Starter: 1,000 Pages)	Approx. 3,000 Letter-Size Pages (Starter: 1,000 Pages)
<b>General</b>		
Power	110 – 127 VAC, 50/60 Hz	110 – 127 VAC, 50/60 Hz
Power Consumption (Average, Sleep)	300 W, 85 W, 12 W (Energy Star Compliant)	300 W, 10 W (Energy Star Compliant)
Safety Certification	UL Safety	UL Safety
Operating Environment	Temperature: 50° – 89°F, Humidity: 20 – 80%	Temperature: 50° – 89.6°F, Humidity: 20 – 80%
Dimensions (W x D x H)	14.3" x 15.7" x 12.1"	14.3" x 15.7" x 12.1"
Weight	21.3 Lbs.	21.3 Lbs.



Product Information: 1-800-921-1202 [www.samsung.com/fax](http://www.samsung.com/fax)  
Product Support: 1-800-SAMSUNG



©2008 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. See [www.samsung.com](http://www.samsung.com) for detailed information. Printed in USA. SF5602/08R4